



CSW24V

Standard Features:

- Power Management System
 - Supplies power when needed to operate the gate and conserves power when not in use
 - Provides exceptional standby time and cycles on battery backup
 - 7 days of standby time or 100 cycles on battery backup
- Fire department compliant: selectable settings allow gate to auto-open upon loss of AC power or battery depletion
- Advanced traffic management control includes Quick-close and Anti-tailgating functions
- Bi-part delay: choose from Standard Operation or Synchronized Close
- Simple-to-set electronic limit system maintains accurate gate position throughout gate travel
- High-density, UV-resistant polycarbonate two-piece cover for excellent heat and corrosion resistance
- Programmable auxiliary relays
- Plug-in loop detectors
- External obstruction sensing; complies with UL325 safety codes
- 5-year commercial warranty; 7-year residential warranty

Specifications:

- 24VDC continuous-duty motor with soft start/stop
- Operator duty rating: continuous
- Power: 110V or 220V Single Phase
- Surge/spike protection
- Gate travel speed: 90-degree opening in 13-15 seconds
- Constructed with 1/4" gold zinc-plated steel for rust prevention
- Weight: 206 lbs.

Optional Features:

- Plug-in loop detectors
- 33AH battery

Battery Backup Operation

BATTERY	CYCLES
2 - 7Ah	100
2 - 33Ah	380

12 ft / 800 lbs Swing Gate

Recommended Capacities

Swing Rating

