




Mfg #	Finish	EZ #
DC6816BC DU	Duronodic	087495
DC6816BC AL	Clear	087494


Regular Arm (Pull Side)
Permits 120° Maximum
Opening



Top Jamb (Push Side)
Permits 120° Maximum
Opening



Parallel Arm (Push Side)
Permits 180° Maximum
Opening



- Sizes and hole patterns match the most popular products on the market.
- Baron closers are "tri-packed", with everything needed for regular, top jamb and parallel arm mounting.
- Heavy Duty Cast Iron Body for years of carefree use.
- Adjustable power from Size 1-6

- Latch & Speed Adjustments for proper closing timing
- Adjustable back check
- Forged steel arms: Forging creates steel parts with more tensile strength, to resist breakage.
- Anti-freeze hydraulic oil for cold climates

- Packed with self-tapping screws, wood screws and sex nuts and bolts for wood, metal, or aluminum door installations.
- U.L. Listed for U.S. and Canada: UL 10C fire rated. Tested to meet ANSI Grade 1 specifications.
- For Cush & Hold Open Cush arms please see page 152.



DP18AL

- For hinge side mount where top rail is less than 3-3/4".
- Requires 2" minimum top rail



DP18PA AL

- For top rails less than 5-1/2".
- Plate requires 2" minimum top rail.



DP18G DU

- Puts top jamb mounted closer flush with top of head frame face
- Requires 1-3/4" minimum head frame.



DP18TJ AL

- Centers top jamb mounted closer vertically.
- Requires 1-3/4" minimum head frame.

Optional DC6816 Closer Mounting Plates

Mfg #	Type	Finish	EZ #
DP18AL	Drop Plate	Clear	091184
DP18DU	Drop Plate	Duronodic	091185
DP18G AL	Top Jamb Flush	Clear	091188
DP18G DU	Top Jamb Flush	Duronodic	091189
DP18PA AL	PA Drop Plate	Clear	100841
DP18PA DU	PA Drop Plate	Duronodic	100842
DP18TJ AL	Top Jamb Vertical	Clear	091186
DP18TJ DU	Top Jamb Vertical	Duronodic	091187