



VIKING



H-10™

UL US
LISTED 187C
UL 325
UL 991

residential and commercial
SLIDE GATE OPERATOR
Class I, Class II, Class III, and Class IV Vehicular Gate Operator

100 CYCLES
in case of power failure*



Innovative Fine Tune Adjustment for the end of gate travel (down to 1/8")




NEW FEATURE!



Built-in lightning protection

Back-driveable unit features direct drive mechanism

Soft-start, soft-stop with adaptive learn algorithm



2000 LB CAPACITY

Easily accessed switch for manual operation



120/220 VAC single phase power source

Easy access to limit switch



Operational Specifications

Operation	24 VDC equivalent to 1HP
Main Power Source	120 / 220 VAC Single Phase
Battery	7 AmpHr 12 VDC x 2
Max Gate Weight	2000 lbs.
Max Gate Length	45 Feet
Max Operating Speed	12" per second
* Battery Backup Operation	100 Full Cycles (1000 lbs. / 20' gate)
Max Duty Cycle	100%
Operating Temperature	-4°F to +158°F

The H-10™ gate operator has the capacity to operate slide gates up to 2000 lbs. and 45 feet in length at 100% duty cycle under extreme conditions. It's efficient mechanism provides a solution for high traffic commercial slide gate applications. The Viking H-10™ gate operator offers efficiency and technology combined in a single package.

WARRANTY
7 years residential
5 years commercial



VIKING
ACCESS SYSTEMS™
vikingaccess.com

800.908.0884